

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

4720/4920 Self-Propelled Sprayers

CAB

AIR FILTER ACTIVATED CARBON – [RE199681](#)

Replace after every 500 hours or annually, whichever occurs first, and as required.

ENGINE

PRIMARY FUEL FILTER (4720) – [RE509036](#)

Replace after every 750 hours or annually.

PRIMARY FUEL FILTER (4920) – [RE531703](#)

Replace after every 500 hours or annually.

ENGINE

PRIMARY AIR FILTER (4720) – [RE196945](#)

Change as required.

PRIMARY AIR FILTER (4920) – [RE164839](#)

Replace filters at least once a year or six cleanings, or if air filter indicator remains ON.

ON BOARD AIR (OBA)

AIR DRYER CARTRIDGE – [AN204967](#)

Replace annually.

ENGINE

SECONDARY AIR FILTER (4720) – [RE181915](#)

SECONDARY AIR FILTER (4920) – [RE172447](#)

Do not clean – change only with Primary Air Filter.

CAB

AIR FILTER RECIRCULATION

ACTIVATED CARBON – [RE199682](#)

Replace every 500 hours or annually, whichever occurs first.

ENGINE

OIL FILTER (4720) – [RE504836](#)

OIL FILTER (4920) – [RE509672](#)

Replace after 100 hours and then after every 250 hours. If Plus-50™ engine oil and a John Deere™ filter are used, the oil and filter service interval may be extended 50 percent, up to 500 hours.

(Click here for [capacity](#))

HYDRAULICS (4720)

HYDRAULIC FILTER – [AN203010](#)

OIL HYDROSTATIC DRIVE – [AN203010](#)

Replace after 500 hours.

(Click here for [capacity](#))

HYDRAULICS (4920)

HYDRAULIC FILTER – [AN203010](#)

up to serial no. 3999

HYDRAULIC FILTER – [AH128449](#)

from serial no. 4000

OIL HYDROSTATIC DRIVE – [AN207368](#)

Please order two.

Replace after 500 hours.

(Click here for [capacity](#))

ENGINE

FUEL IN-LINE STRAINER (4920) – [AR103220](#)

Replace and clean as required.

ENGINE

SECONDARY FUEL FILTER (4720) – [RE509032](#)

Replace after every 750 hours.

SECONDARY FUEL FILTER (4920) – [RE522688](#)

Replace after every 500 hours or annually.



JOHN DEERE

Genuine Parts and Service

https://www.deere.com/en_US/parts/parts_by_industry/ag/fmi/filter_maintenance_information.page

CAPACITIES

4720/4920 Self-Propelled Sprayers

CAPACITIES (Approximate):

Fuel Tank:

4720.....	360 L (95 gal)
4920.....	518 L (137 gal)

Cooling System with Heater:

Cool-Gard™

4720.....	24 L (6.3 gal)
4920.....	34 L (9 gal)

Crankcase including Filter:

Plus-50™

4720.....	26 L (6.7 gal)
4920.....	29 L (7.7 gal)

Hydraulic Reservoir:

Torq-Gard™ Supreme

4720.....	64 L (17 gal)
4920.....	76 L (20 gal)

Hydraulic System:

Torq-Gard™ Supreme

4720.....	163 L (43 gal)
4920 (Hydraulic and Hydrostatic).....	163 L (43 gal)

Final Drives (Front Hubs) Each:

GL-5

4720.....	1.2 L (0.32 gal)
4920.....	2.5 L (0.66 gal)

Final Drives (Rear Hubs) Each:

GL-5

4720.....	1.2 L (0.32 gal)
4920.....	2.5 L (0.66 gal)

[Return to Filter Overview](#)

