

# FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

## A400 and R450 Series Windrowers

### ENGINE

#### PRIMARY AIR FILTER (A400 AND R450) – [AT300487](#)

Replace after every 250 hours or each season whichever occurs first.



### ENGINE

#### SECONDARY AIR FILTER (A400 AND R450) – [AT314583](#)


Replace after every 250 hours or each season whichever occurs first.



### CAB

#### RECIRCULATION AIR FILTER (A400 AND R450) – [H220870](#)

Clean every 250 hours or annually, whichever comes first, and replace annually or as required.



### ENGINE

#### FUEL TANK VENT FILTER [H216169](#)


Replace after every 500 hours or annually whichever comes first.



### CAB

#### FRESH AIR FILTER (A400 AND R450) – [AH115833](#)

Clean every 250 hours or annually, whichever comes first, and replace annually or as required.



### ENGINE

#### FUEL FILTER (A400 AND R450) – [RE522878](#) (Final)

#### FUEL FILTER (A400 AND R450) [RE541922](#) (Primary)

Replace every 500 hours or annually, whichever comes first.



### ENGINE

#### OIL FILTER (A400 AND R450) – [RE504836](#)

Replace after 100 hours and then every 250 hours or annually, whichever comes first.

If John Deere Plus-50™ II oil is used, along with a John Deere oil filter, the oil change interval may be extended by 250 hours.

If John Deere Plus-50™ oil is used, along with a John Deere oil filter, the oil change interval may be extended by 125 hours.

(Click here for [capacity](#))



### HYDRAULIC

#### HYDRAULIC FILTER (A400 AND R450) – [AH128449](#)

Replace after every 400 hours or annually, whichever comes first.

(Click here for [capacity](#))



**JOHN DEERE**  
Genuine Parts and Service

[http://www.deere.com/en\\_US/parts/service/support/filteroverviews.html](http://www.deere.com/en_US/parts/service/support/filteroverviews.html)

# CAPACITIES

## A400 and R450 Series Windrowers

### CAPACITIES (Approximate):

#### Fuel Tank:

A400 .....	477 L (126 gal)
R450 .....	477 L (126 gal)

#### Cooling System:

##### Cool-Gard™ II Premix

A400 .....	29.3 L (7.74 gal)
------------	-------------------

#### Engine Oil:

##### Plus-50™ II

A400 .....	13 L (3.43 gal)
------------	-----------------

#### Engine Oil with Filter:

##### Plus-50™ II

R450 .....	19 L (5.02 gal)
------------	-----------------

#### Radiator Capacity:

R450 .....	33.1 L (8.75 gal)
------------	-------------------

#### Hydraulic System (Reservoir):

##### Hy-Gard™

.....	95 L (25 gal)
Including Hoses, Valves, and Pumps .....	129 L (34 gal)

#### Final Drives (Each Side):

##### GL-5

.....	2.1 L (0.46 gal)
-------	------------------

#### Pump Drive Gear Case:

##### Hy-Gard™

.....	3.8 L (1 gal)
-------	---------------

[Return to Filter Overview](#)

