

ROLLER LEVEL

RL84



JOHN DEERE



Roller Level

RL84



Specifications

- The Worksite Pro™ Roller Level delivers reliable, cost-efficient productivity for finish-grade work.
- Designed for minimal maintenance and maximum uptime, with only two greasable bearings, two replaceable cutting edges, and no hydraulics.
- Roller pulverizes clumps and clods for a smoother finish in loose soil.
- Front roller position offers unobstructed visibility and provides total control when contouring, grading, cutting, and smoothing flat or significantly sloped terrain.
- Front and rear cutting edges make quick work of tough site-prep and grading tasks. Use either or both edges to spread loose material and for quickly cutting or scraping hard-pack without disturbing the base below.
- Like all Worksite Pro™ attachments, this roller level is optimized to work with John Deere G- and E-Series Skid Steers and Compact Track Loaders (CTLs). It's also compatible with many competitive models. See your local Deere dealer for details.

	RL84
Weight	734 kg (1,620 lb.)
Width	
Overall	2367 mm (93.3 in.)
Box	2133 mm (84 in.)
Length	1694 mm (66.7 in.)
Height	650 mm (25.6 in.)
Cutting Edge, Bolt-On (2)	Standard
Front	16 x 152 x 2134 mm (0.625 x 6 x 84 in.)
Rear	16 x 152 x 2134 mm (0.625 x 6 x 84 in.)
Roller Diameter	330 mm (13 in.)
Hydraulics	No
Greasable Bearings (2)	Standard
Vehicle Compatibility	324E, 330G, and 332G Skid Steers; 317G, 323E, 331G, and 333G CTLs

WORKSITE PRO

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

