

# SNOW BLOWERS



JOHN DEERE

*SB60B | SB72B | SB78B | SB84B | SB72D | SB78D | SB84D | SB84H*



# SNOW BLOWERS

SB60B | SB72B | SB78B | SB84B |  
SB72D | SB78D | SB84D | SB84H



## Specifications

- Two-stage hydraulic snow blowers are ideal for clearing or throwing snow up to 13.7 m [45 ft.] from roadways, parking lots, driveways, or sidewalks.
- Case-drain connection is not required on standard- or high-flow models.
- Direct-drive motors at auger and impeller provide robust and reliable performance with fewer parts.
- 635-mm (25 in.) (B-Series) or 915-mm (36 in.) (D-Series/H-Series) high-volume intake shroud maximizes productivity.
- Hydraulically actuated, poly-lined chute and deflector enable easy snow placement via in-cab controls.
- Chute rotates 270 degrees using a simple, direct-drive hydraulic motor rather than a chain-and-sprocket design or cables.
- Easily adjustable skid shoes adjust to cutting-edge height to accommodate different surfaces. Replaceable bolt-on wear-resistant tapered-steel edges and poly edges are available.
- D-Series Snow Blowers introduce a new serrated-auger option to cut through the heaviest snow conditions.
- Like all John Deere attachments, these snow blowers are optimized to work with John Deere skid steer loaders (SSLs), compact track loaders (CTLs), and compact wheel loaders (CWLs). They're also compatible with many competitive models. See your local Deere dealer for details.

Model	SB60B	SB72B	SB78B	SB84B	SB72D	SB78D	SB84D	SB84H
Weight	360 kg (795 lb.)	380 kg (845 lb.)	400 kg (878 lb.)	410 kg (895 lb.)	520 kg (1,150 lb.)	540 kg (1,195 lb.)	560 kg (1,230 lb.)	610 kg (1,340 lb.)
Overall Length	965 mm (38 in.)	965 mm (38 in.)	965 mm (38 in.)	965 mm (38 in.)	1090 mm (43 in.)	1090 mm (43 in.)	1090 mm (43 in.)	1090 mm (43 in.)
Overall Width	1550 mm (61 in.)	1885 mm (73 in.)	2010 mm (79 in.)	2010 mm (79 in.)	1920 mm (76 in.)	2070 mm (82 in.)	2225 mm (88 in.)	2210 mm (87 in.)
Overall Height	1450 mm (57 in.)	1450 mm (57 in.)	1450 mm (57 in.)	1450 mm (57 in.)	1980 mm (78 in.)	1980 mm (78 in.)	1980 mm (78 in.)	1980 mm (78 in.)
Intake Width	1525 mm (60 in.)	1830 mm (72 in.)	1980 mm (78 in.)	2135 mm (84 in.)	1830 mm (72 in.)	1980 mm (78 in.)	2135 mm (84 in.)	2120 mm (84 in.)
Intake Height	635 mm (25 in.)	635 mm (25 in.)	635 mm (25 in.)	635 mm (25 in.)	915 mm (36 in.)	915 mm (36 in.)	915 mm (36 in.)	915 mm (36 in.)
Auger Diameter	355 mm (14 in.)	355 mm (14 in.)	355 mm (14 in.)	355 mm (14 in.)	455 mm (18 in.)	455 mm (18 in.)	455 mm (18 in.)	455 mm (18 in.)
Fan Diameter	455 mm (18 in.)	455 mm (18 in.)	455 mm (18 in.)	455 mm (18 in.)	660 mm (26 in.)	660 mm (26 in.)	660 mm (26 in.)	660 mm (26 in.)
Maximum Throw Distance	12.2 m (40 ft.)	12.2 m (40 ft.)	12.2 m (40 ft.)	12.2 m (40 ft.)	13.7 m (45 ft.)	13.7 m (45 ft.)	13.7 m (45 ft.)	13.7 m (45 ft.)
Discharge-Chute Control	Electric over hydraulic	Electric over hydraulic	Electric over hydraulic	Electric over hydraulic	Electric over hydraulic	Electric over hydraulic	Electric over hydraulic	Electric over hydraulic
Chute Rotation	270 deg.	270 deg.	270 deg.	270 deg.	270 deg.	270 deg.	270 deg.	270 deg.
<b>Hydraulics</b>								
Required Hydraulics	Standard flow	Standard flow	Standard flow	Standard flow	High flow	High flow	High flow	High flow
Auger Motors	Single	Single	Single	Single	Single	Single	Single	Dual
<b>Required Flow</b>								
Minimum	53 l/min (14 gpm)	53 l/min (14 gpm)	68 l/min (18 gpm)	68 l/min (18 gpm)	114 l/min (30 gpm)	114 l/min (30 gpm)	114 l/min (30 gpm)	114 l/min (30 gpm)
Maximum	79 l/min (21 gpm)	79 l/min (21 gpm)	102 l/min (27 gpm)	102 l/min (27 gpm)	159 l/min (42 gpm)	159 l/min (42 gpm)	159 l/min (42 gpm)	159 l/min (42 gpm)
Maximum Operating Pressure	24 100 kPa (3,500 psi)	24 100 kPa (3,500 psi)	24 100 kPa (3,500 psi)	24 100 kPa (3,500 psi)	24 100 kPa (3,500 psi)	24 100 kPa (3,500 psi)	24 100 kPa (3,500 psi)	24 100 kPa (3,500 psi)
<b>Vehicle Compatibility*</b>	316GR and 318G SSLs; 317G CTL	316GR, 318G, 320G, and 324G SSLs; 317G and 325G CTLs; 204L and 304L CWLs	320G, 324G, 330G, and 332G SSLs; 325G, 331G, and 333G CTLs; 244L and 324L CWLs	330G and 332G SSLs; 325G, 331G, and 333G CTLs; 244L and 324L CWLs	320G and 324G SSLs; 325G CTL	320G, 324G, 330G, and 332G SSLs; 325G, 331G, and 333G CTLs; 244L and 324L CWLs	330G and 332G SSLs; 325G, 331G, and 333G CTLs; 324L CWL	330G and 332G SSLs; 325G, 331G, and 333G CTLs; 324L CWL

\*Hydraulic connection requires 12.7-mm (0.5 in.) quick-connect couplers. / †Electrical connection requires 14-pin Deutsch.

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.



JohnDeere.com