

# VIBRATORY ROLLERS



JOHN DEERE

VR66C | VR73C | VR84C



# VIBRATORY ROLLERS

VR66C | VR73C | VR84C



## Specifications

- John Deere vibratory rollers turn a skid steer loader (SSL), compact track loader (CTL), or compact wheel loader (CWL) into a powerful compactor. Ideal for asphalt patch, foundation, trench, and flatwork compaction, they're very economical since owning one eliminates the costs and maintenance of a self-propelled roller.
- Powered by standard hydraulics, vibratory rollers produce compaction forces up to 4260 kg (9,370 lbf).
- With drum oscillation of  $\pm 15$  deg. these attachments are easy to maneuver.
- Quik-Tatch™ compatible, they take only one minute to hook up.
- Drum and shaft bearings are lubricated and cooled in oil bath for long life.
- Bidirectional operation increases productivity.
- Like all John Deere attachments, these vibratory rollers are optimized to work with John Deere SSLs, CTLs, and CWLs. They're also compatible with many competitive models. See your local Deere dealer for details.

	VR66C	VR73C	VR84C
<b>Overall width</b>	1.8 m (72 in.)	2.0 m (79 in.)	2.3 m (90 in.)
<b>Overall length</b>	99 cm (39 in.)	99 cm (39 in.)	99 cm (39 in.)
<b>Overall height</b>	79 cm (31 in.)	79 cm (31 in.)	79 cm (31 in.)
<b>Drum width</b>	1.7 m (66 in.)	1.8 m (73 in.)	2.1 m (84 in.)
<b>Drum diameter</b>			
Smooth	61.0 cm (24 in.)	61.0 cm (24 in.)	61.0 cm (24 in.)
Sheep's-foot (without pads)	51.0 cm (20 in.)	51.0 cm (20 in.)	N/A
<b>Drum oscillation</b>	$\pm 15$ deg.	$\pm 15$ deg.	$\pm 15$ deg.
<b>Dynamic force</b>	3538 kg (7,800 lbf)	3878 kg (8,550 lbf)	4250 kg (9,370 lbf)
<b>Vibrations per minute</b>			
Range	41–95 L/min. (11–25 gpm)	41–95 L/min. (11–25 gpm)	41–95 L/min. (11–25 gpm)
Optimum performance	75.7 L/min. (20 gpm)	75.7 L/min. (20 gpm)	75.7 L/min. (20 gpm)
<b>Operating weight</b>			
Smooth drum	975 kg (2,150 lb.)	1043 kg (2,300 lb.)	1148 kg (2,530 lb.)
Sheep's-foot drum	945 kg (2,085 lb.)	1012 kg (2,230 lb.)	N/A
<b>Vehicle Compatibility</b>			
Smooth drum	312GR, 314G, 316GR, 318G, 320G, 324G, 330G, and 332G SSLs; 317G, 325G, 331G, and 333G CTLs	330G and 332G SSLs; and 317G, 325G, 331G, and 333G CTLs	330G and 332G SSLs; 325G, 331G, and 333G CTLs; 244L and 324L CWLs
Sheep's-foot drum	312GR, 314G, 316GR, 318G, 320G, 324G, 330G, and 332G SSLs; and 317G, 325G, 331G, and 333G CTLs	330G and 332G SSLs; and 317G, 325G, 331G, and 333G CTLs	N/A

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

