

ROLLOUT BUCKETS



JOHN DEERE

RB72 | RB84 | RB96



ROLLOUT BUCKETS

RB72 | RB84 | RB96



SPECIFICATIONS

- Quality-manufactured Worksite Pro rollout buckets feature an open design that enables quick, clean, and easy material loading.
- Available in a range of three sizes, rollout buckets are ideal for achieving elevated dump heights in high-capacity applications, including construction, forestry, agriculture, demolition, recycling, and land management.
- Each model comes standard with a universal bolt-on cutting edge that is double beveled and reversible, for extended wear life.
- Industrial-strength, high-pressure cylinders are cushioned for smooth bucket operation and are constructed with induction-hardened, double chrome-plated rods for maximum durability.
- Like all Worksite Pro attachments, these rollout buckets are optimized to work with John Deere skid steer loaders (SSLs), compact track loaders (CTLs), and compact wheel loaders (CWLs). They're also compatible with many competitive models. See your local Deere dealer for details.

| Model | RB72 | RB84 | RB96 |
|-----------------------------------|---|--|---|
| Weight | 532 kg (1,170 lb.) | 580 kg (1,275 lb.) | 618 kg (1,360 lb.) |
| Width | 1850 mm (73 in.) | 2150 mm (84.75 in.) | 2480 mm (97.5 in.) |
| Height | 820 mm (32.3 in.) | 820 mm (32.3 in.) | 820 mm (32.3 in.) |
| Length | 1270 mm (50 in.) | 1270 mm (50 in.) | 1270 mm (50 in.) |
| Heaped Capacity | 0.91 m ³ (1.19 cu. yd.) | 1.10 m ³ (1.44 cu. yd.) | 1.28 m ³ (1.68 cu. yd.) |
| Dump Reach | 860 mm (34 in.) | 860 mm (34 in.) | 860 mm (34 in.) |
| Dump Angle | 114 deg. | 114 deg. | 114 deg. |
| HYDRAULIC CYLINDER | | | |
| Pivot Pin Diameter | 38 mm (1.5 in.) | 38 mm (1.5 in.) | 38 mm (1.5 in.) |
| Bore Diameter | 64 mm (2.5 in.) | 64 mm (2.5 in.) | 64 mm (2.5 in.) |
| Rod Diameter | 38 mm (1.5 in.) | 38 mm (1.5 in.) | 38 mm (1.5 in.) |
| Maximum Operating Pressure | 25 000 kPa (3,625 psi) | 25 000 kPa (3,625 psi) | 25 000 kPa (3,625 psi) |
| BOLT-ON CUTTING EDGE | | | |
| Length | 200 mm (8.0 in.) | 200 mm (8.0 in.) | 200 mm (8.0 in.) |
| Thickness | 19 mm (0.75 in.) | 19 mm (0.75 in.) | 19 mm (0.75 in.) |
| Vehicle Compatibility | 312GR, 314G, 316GR, 318G, 320E, and 324E SSLs; 317G and 323E CTLs | 330G and 332G SSLs; 323E, 331G, and 333G CTLs; 204L, 244K-II, 304L, and 324K CWLs* | 330G and 332G SSLs; 331G and 333G CTLs; 204L, 244K-II, 304L, and 324K CWLs* |

*CWLs require skid steer-style quick coupler for operation.

WORKSITE PRO

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

