

310B BACKHOE LOADER

12,519 lb (5678 kg)

Transport Height.....	11 ft 3 in. (3.43 m)
Transport Length.....	23 ft 7 in. (7.19 m)
Machine Width.....	6 ft 10 in. (2.08 m)

ENGINE.....John Deere 300 Series

Number of Cylinders and Displacement.....	4 cylinders, 219 cu in. (3.6 L)
Air Intake System.....	Naturally aspirated
Bore and Stroke.....	4.02 x 4.33 in. (102 x 110 mm)
Net hp at 2500 rpm.....	58 SAE hp (43.3 kW) DIN 45.4 kW or 62 SAE hp (46.2 kW) DIN 49 kW
Maximum Torque at 1300 rpm.....	150 lb-ft (203 N•m) or 160 lb-ft (217 N•m)
Nozzle Opening Pressure:	
New.....	3200 ± 50 psi (22 065 ± 345 kPa)
Used.....	3000 ± 50 psi (20 685 ± 345 kPa)
Valve Clearance (Cold):	
Intake.....	0.014 in. (0.36 mm)
Exhaust.....	0.018 in. (0.46 mm)
Oil Pressure at 2500 rpm.....	50 ± 15 psi (345 ± 105 kPa)
Static Injection Pump Timing.....	Timing lines aligned w/ flywheel located at TDC
Dynamic Injection Pump Timing at Rated Load rpm*.....	17 + 0 - 1° BTDC
Speeds:	
Slow Idle.....	800 ± 25 rpm
Fast Idle.....	2675—2700 rpm
Full Load Rating.....	2500 rpm
Cylinder Pressure Hot (Min).....	350 psi (2415 kPa) cranking w/ injectors removed
Flywheel Teeth.....	142

Note: *For latest information, see Dealer Technical Assistance Center (DTAC) Solution K000413.

TRANSMISSION

Model and Speeds.....	Collar shift w/ hydraulic reverser: 8 forward, 8 reverse
Pump Flow (Min) Used, at 150 psi (1035 kPa) and 2200 rpm.....	10.5 gpm (0.66 L/s)
Reverser System Pressure at Fast Idle.....	155—165 psi (1070—1140 kPa)
Lube Pressure (Clutch Pedal Depressed).....	8—10 psi (55—69 kPa)
Clutch Operating Pressure.....	155—165 psi (1070—1140 kPa)
Filter Relief Pressure.....	50 psi (345 kPa) differential

HYDRAULIC SYSTEM—Close-Center

Pump:	
Size.....	4.0 cu in. (65 cm ³)
Flow (Min).....	30.5 gpm (115 L/s) used at 2000 psi (13 790 kPa) and 2200 rpm
Standby Pressure.....	2300—2400 psi (15 860—16 550 kPa)
Charge Pressure at Fast Idle.....	55—130 psi (380—900 kPa)
Accumulator Charge Pressure.....	500 psi (3450 kPa)
Surge Relief Pressure.....	150 psi (1035 kPa)
Filter Relief Pressure.....	50 psi (345 kPa) differential
Priority Valve Setting at 1000 rpm.....	1300 ± 50 psi (8895 ± 345 kPa)
Cooler Bypass Valve:	
Relieves to Lubrication.....	120 psi (830 kPa)
Relieves to Sump.....	130 psi (895 kPa)

Continued on next page

RELIEF VALVE SETTINGS

Loader Circuit Relief Valves:

Auxiliary	2500 psi (17 240 kPa)
Bucket Dump	1500 psi (10 305 kPa)
Bucket Rollback.....	2750 psi (18 960 kPa)

Backhoe Circuit Relief Valves:

Boom Lower	2375 psi (16 380 kPa)
Boom Raise	3500 psi (24 135 kPa)
Crowd	2375 psi (16 375 kPa)
Swing Right and Left	2375 psi (16 375 kPa)

CYCLE TIMES (At Fast Idle)

Oil Temperature 150 ± 10°F (65 ± 5°C)

Loader Function:

Boom Down (Float)	3.5 sec
Boom Down (Power)	2.5 sec
Boom Raise	3.4 sec
Bucket Dump (Boom at Full Height).....	1.4 sec
Bucket Rollback (Flat on Ground)	0.6 sec
Bucket Rollback (From Maximum Dump Position and Boom at Full Height).....	1.2 sec

Backhoe Functions:

Boom Lower (Full Height to Ground).....	1.6 sec
Boom Lower (Full Height to Maximum Depth)	3.4 sec
Boom Raise (Ground to Full Height)	1.9 sec
Boom Raise (Maximum Depth to Full Height)	4.0 sec
Bucket Curl	2.3 sec
Bucket Dump	1.8 sec
Dipperstick In.....	2.8 sec
Dipperstick Out.....	2.7 sec
Swing (180°).....	3—5 sec

LUBRICANTS

See front of this book for the codes [].

CAPACITIES

	U.S.	Imp.	Metric
Engine:			
Cooling System [N]	4 gal	2.5 gal	11.4 L
Crankcase w/ Filter [E].....	9 qt	7.5 qt	8.5 L
Transmission (Refill) [C]	8.5 gal	7.1 gal	32.0 L
Transmission and Hydraulic System [C].....	20.5 gal	17.1 gal	77.6 L
Fuel Tank	19.5 gal	16.3 gal	73.8 L

TIRE PRESSURE (Cold Inflation)

Tire Size	Type	Rating	Normal Pressure
Front:			
7.50-16	F3	10 ply	60 psi (415 kPa)
11L-15	F3	8 ply	44 psi (305 kPa)
Rear:			
16.9-24	R4	8 ply	28 psi (195 kPa)
19.5L-24	R4	8 ply	24 psi (165 kPa)
19.5L—24	R4	10 ply	28 psi (195 kPa)