

# SPECIFICATIONS

# 360-DEGREE VISIBILITY IS YOUR WINDOW OF OPPORTUNITY.

www.skidsteer.com

## 260 Series II Skid Steer

- Patented vertical-lift system with cushioned boom cylinders provides greater reach than conventional skid steers, for precise center load placement and quick, efficient truck loading.
- 72-hp John Deere 3029T high-torque, turbo-charged engine with direct injection has exclusive wet-sleeve design, high-ring pistons, and precision joint-connecting rods. This easy-starting, durable engine is extremely fuel efficient.
- Optional two-speed (up to 12 mph) transmission is available for increased productivity.
- Quick-lift cab, removable side panels, and easy-access top and rear doors permit convenient maintenance and service.
- Superior 360-degree visibility results in greater productivity and safe operation. Unique boom arm design provides maximum bucket visibility.
- Steep 45-degree dump angle and high 35-degree bucket rollback make for more efficient load carrying and quicker cycle times.
- Available cab enclosure, air conditioner, and heater/defroster provide year-round climate control.
- Optional hydraulic Quik-Tatch™ latches/unlatches at the touch of a switch for convenient in-the-seat attachment switchover.
- Strong machine forces include — 7,500-lb. bucket breakout, 4,800-lb. boom breakout, 5,750-ft.-lb. axle torque, and 5,000-lb. tipping load. Rated Operating Capacity (R.O.C.) is 2,400 lb. (2,600 lb. with optional counterweight).
- 127-in. hinge pin height easily clears 10-ft. truck sideboards for fast, efficient truck loading.

	260 Series II	Standard Equipment	Options/Accessories
<b>Engine</b> . . . . .	John Deere	Adjustable Armrests, Patent Pending	Air Conditioning with Heater/Defroster
Model . . . . .	3029T	Adjustable Foot Pedals	Auto Preheat
Displacement . . . . .	179 cu. in. (2.9 L)	Air Heat Cold Start	Auto Shutdown with Alarm
Cylinders . . . . .	3	Auxiliary Hydraulics	Backup Alarm
Horsepower . . . . .	72.4 hp (54 kW) gross / 69 hp (51.5 kW) net	Convenient Front and Rear Tie Downs	Block Heater Kit
Rated Engine Speed . . . . .	2,400 rpm	Deluxe Seat	Cab Enclosure
Fuel Capacity . . . . .	20 U.S. gal. (76 L)	Four Grab Handles	Demolition Door Kit
<b>Performance:</b>		Front and Rear Work Lights	Dual Flashers Kit
SAE Rated Operating Capacity . . . . .	2,400 lb. (1089 kg)	Integral Cab Boom Locks	Floor Cover Plates
With Optional Counterweights . . . . .	2,600 lb. (1180 kg)	John Deere Manufactured Hydraulic Cylinders	Hand Controls
Tipping Load . . . . .	5,000 lb. (2268 kg)	Meters/Gauges/Warning Lights	Heater/Defroster Kit
<b>Breakout Force:</b>		Patented John Deere Quik-Tatch	High-Flow Hydraulics
Heavy-Duty Foundry Bucket . . . . .	7,500 lb. (3402 kg)	Patented Vertical-Lift Boom	Horn
Heavy-Duty Construction Bucket . . . . .	5,300 lb. (2404 kg)	Quick-Pivot ROPS	Hydraulic Quik-Tatch
<b>Ground Speed:</b>		Rear Window	Hydraulic Self-Leveling Kit
Single Speed . . . . .	7.0 mph (11.3 km/h)	Seat Belt with Auto Recoil	Quik-Tatch Weights
Two-Speed, Low . . . . .	7.0 mph (11.3 km/h)	Triple Interlock Control System	Rear Weight Brackets
Two-Speed, High . . . . .	12.0 mph (19.3 km/h)	Turbocharged John Deere POWERTECH® Engine	Rearview Mirror Kit
Maximum Axle Torque . . . . .	5,750 ft.-lb. (7796 Nm)	Wet Disk Brakes	Shoulder Belt
Operating Weight . . . . .	8,250 lb. (3742 kg)	12 pr. 14x17.5 SKS Extra-Wall Tires	Side Window Kit
<b>Hydraulics:</b>		55-Amp Alternator	SMV Sign
Hydraulic Pressure . . . . .	3,100 psi		Suspension Seat
<b>Hydraulic Pump:</b>			Top Window
Standard Flow . . . . .	21.3 gpm (80.6 L/min.)		Vinyl Cab Enclosure
High Flow . . . . .	33.1 gpm (125.3 L/min.)		Warning Beacon
<b>Hydraulic Horsepower:</b>			2-Speed Transmission
Standard Flow . . . . .	38.5 hp (28.7 kW)		3-Inch Seat Belt
High Flow . . . . .	59.9 hp (44.7 kW)		8-Button Handle
<b>Transmission</b> . . . . .	Hydrostatic four-wheel drive		12-Volt Receptacle Kit
<b>Dimensions:</b>			
Length without Bucket . . . . .	115 in. (2921 mm)		
Length with Bucket . . . . .	138 in. (3504 mm)		
Width without Bucket . . . . .	76.2 in. (1935 mm)		
Height to ROPS . . . . .	82.9 in. (2105 mm)		
Height to Hinge Pin . . . . .	127 in. (3226 mm)		
<b>Dump Reach :</b>			
Heavy-Duty Foundry Bucket . . . . .	32 in. (813 mm)		
Heavy-Duty Construction Bucket . . . . .	39 in. (991 mm)		
Dump Angle (At Full Height) . . . . .	45 degrees		
Bucket Rollback (At Ground) . . . . .	35 degrees		
Wheelbase . . . . .	47.6 in. (1209 mm)		
Ground Clearance . . . . .	11 in. (280 mm)		
Angle of Departure . . . . .	27 degrees		
Standard Tire Size . . . . .	14x17.5 SKS Extra-Wall, 12-ply rating		

### John Deere Worksite Pro™ Attachments

- |   |                       |                      |
|---|-----------------------|----------------------|
| Ag Utility Grapple  | Hydraulic Breakers    | Snow/Utility Blades  |
| Angle Brooms  | Multi-Purpose Buckets | Three-Point Hitch    |
| Augers  | Pallet Forks          | Tined/Brush Grapples |
| Backhoes  | Pick-Up Brooms        | Tooth Bars           |
| Bale Spear  | Power Rakes           | Tracks               |
| Cold Planers  | Rotary Tillers        | Trenchers            |
| Construction, Foundry, Manure/Slurry, and Utility Buckets | Scrap Grapples        | Vibratory Rollers    |

Due to various widths, not all attachment sizes offered are compatible with all 200 Series Skid Steers.

**John Deere Standard Warranty** . . . . . 1-year unlimited hours  
(Dimensions and specifications in accordance with SAE and ISO standards. Rated Operating Capacity with 78-in. Heavy-Duty Foundry Bucket and standard tires per SAE Standard J818.)

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.



JOHN DEERE