### REPLACEMENT PARTS GUIDE

1R Series - 1025R Compact Utility Tractor (HJ100001 - ) (Worldwide Edition)

#### **ENGINE**



# OIL FILTER M806418

Replace every 200 hours and annually if less than 200 hours of operation.



#### INLINE FUEL FILTER AM116304

Replace every 400 hours and annually



# FUEL FILTER MIU804763

annually.

Replace every 400 hours and



PRIMARY AIR FILTER M131802 ( - JJ153036) LVU34503 (JJ153037 - )

SECONDARY AIR FILTER M131803 ( - JJ153036) LVU34504 (JJ153037 - )

Replace every 400 hours and as required. Check and service every 10 hours/daily, every 200 hours and annually. (Service 1025R, 1026R when restriction indicator is red).



#### **TRANSMISSION**



### HYDRAULIC FILTER LVA16054

Replace after first 50 hours and every 200 hours.





M806418, LVA16054, AM116304, M131802, MIU804763

#### TA15270 (JJ153037 - )

M806418, LVA16054, AM116304, LVU34503. MIU804763

Each kit contains above filters and offering a complete solution for your maintenance needs to keep your tractor running at peak performance.



# **CAPACITIES**

# 1R Series - 1025R Compact Utility Tractor (HJ100001 - ) (Worldwide Edition)

CAPACITIES (Approximate):	
Fuel Tank:	
21.2 L (5.6 gal)	
Cooling System: Cool-Gard™ II	
Crankcase with Filter: Plus-50™	
2.7 L (0.71 gal)	

Hy-Gard™	
	12.3 L (3.3 gal)
Front Axle: Hy-Gard™	
	2.8 L (0.74 gal)



### REPLACEMENT PARTS GUIDE

1R Series - 1025R Compact Utility Tractor (HJ100001 - ) (Worldwide Edition)





CLUTCH DISK LVA15954



BATTERY TA15224



BRAKE DISK LVA16465



ALTERNATOR <u>AUC13336</u> (40 A) <u>MIA884643</u> (55 A)

**FAN BELT DRIVE** 



M805011 (LGTH = 927 mm) LVU21854 (LGTH = 3076 mm) LVU21853 (LGTH = 2940 mm) TCU16122 (LGTH = 2540 mm)

<u>UC20041</u> (LGTH = 2276 mm)







SEAT

<u>LVA16945</u> (BACK)

<u>LVA19114</u> (BOTTOM)





TIE ROD MIA881641

