

# FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

5E Tier 2, Tier 3, iT4 and FT4 Series Utility Tractors (North American Version) – 5045E, 5055E, 5065E, 5075E


## CAB (If Equipped)

FRESH AIR FILTER (2)  
[RE198488](#)

RECIRCULATION AIR FILTER (2)  
[RE195491](#)

RECIRCULATION W/O A.C. AIR  
FILTER – [R198887](#)


Clean after every 500 hours and  
change every 1200 hours.



## ENGINE (If Equipped)

DIESEL PARTICULATE FILTER  
(DPF) [RE567056](#)

Replace as required.




## ENGINE AIR

PRIMARY AIR FILTER  
(T2, iT4 ENGINE) [RE282286](#)  
(FT4) [SU29300](#)

SECONDARY AIR FILTER  
(T2, iT4 ENGINE) [RE282287](#)  
(FT4) [SU29301](#)

Service after every 250 hours or annually,  
and as required per conditions.




## HYDRAULIC

OIL FILTER [RE45864](#)

Replace after initial 100 hours,  
then every 250 hours and every  
1200 hours.

(Click here for [capacity](#))



## ENGINE

OIL FILTER [RE519626](#)

Replace after initial 100 hours, then  
every 250 hours or annually.

If Plus-50™ II oil and John Deere™  
filter is used interval may be extended  
to 500 hours.

(Click here for [capacity](#))



## ENGINE

FUEL FILTER  
[RE60021](#) (Tier 2, iT4)  
[R536698](#) (FT4)

Replace after every 500 hours.



**JOHN DEERE**

Genuine Parts and Service

# CAPACITIES

## 5E Tier 2, Tier3, iT4 and FT4 Series Utility Tractors (North American Version) – 5045E, 5055E, 5065E, 5075E

### CAPACITIES (Approximate):

#### Fuel Tank:

Open Station.....	68 L (18 gal)
Cab.....	82 L (21.6 gal)

#### Cooling System:

##### Cool-Gard™ II

.....	9.5 L (2.5 gal)
-------	-----------------

#### Engine Oil:

##### Plus-50™ II

.....	8.5 L (2.24 gal)
-------	------------------

#### Transmission and Hydraulic System Oil:

##### Hy-Gard™

Trans Sync Shuttle .....	38 L (10 gal)
PowrReverser.....	43.5 L (11.5 gal)

#### Mechanical Front Wheel Drive (MFWD):

##### Hy-Gard™

Wheel Hub (Each) .....	0.8 L (0.21 gal)
Axle Housing .....	4.5 L (1.18 gal)

[Return to Filter Overview](#)

