


# FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

## 5M Series Final Tier 4 (FT4) Tractors - 5075M, 5085M, 5100M, 5115M

### CAB

**FRESH AIR FILTER**  
[RE198488](#)


Clean every 600 hours, annually, and as required per conditions (if equipped).



### CAB

**RECIRCULATION AIR FILTER**  
[RE195491](#)

Clean every 600 hours, annually, and as required per conditions (if equipped).



### ENGINE

**SECONDARY FUEL FILTER**  
(5085M-5115M) [RE551508](#)

Service filter after 10 hours.  
Replace every 500 hours.



### ENGINE

**FUEL TANK VENT FILTER**  
[H216169](#)

Clean every 1200 hours. Replace if damaged.



### ENGINE

**DIESEL EXHAUST FLUID (DEF) DOSING UNIT FILTER**  
(5085M-5115M) [RE554498](#)


Replace within first five years and every 4500 hours.



### ENGINE

**FUEL FILTER**  
(5075M) [R536698](#)

Service filter after 10 hours.  
Replace every 500 hours.




### ENGINE

**DIESEL PARTICULATE FILTER (DPF)**  
(5075M)  
[RE567056](#)

(5075M OOS (100101-), CAB (400101-)  
[RE568454](#)

Replace as required.




### TRANSMISSION

**HYDRAULIC FILTER**  
[SJ11784](#)

Replace after 100 hours and every 600 hours.


(Click here for [capacity](#))



### ENGINE

**OPEN CRANKCASE VENT (OCV) FILTER**  
(5085M-5115M) [DZ105796](#), [DZ105100](#)

Replace as required.



### ENGINE

**PRIMARY FUEL FILTER**  
(5085M-5115M) [RE551507](#)

Service filter after 10 hours.  
Replace every 500 hours.



### ENGINE

**OIL FILTER**  
(5075M) [RE519626](#)  
(5085M-5115M) [RE504836](#)

Replace after initial 100 hours, then every 250 hours or annually. If Plus-50™ II oil and John Deere™ filter is used interval may be extended to 500 hours.

(Click here for [capacity](#))





### ENGINE

**SECONDARY AIR FILTER**  
[RE253519](#)

**PRIMARY AIR FILTER**  
(5075M CAB (TSN -400100))  
[RE253518](#)

(5075M CAB (TSN 400101-), OOS (TSN 100101-))  
(5085M-5115M)  
[SU20768](#)

Service every 1200 hours or as required per conditions.



**JOHN DEERE**

Genuine Parts and Service

# CAPACITIES

## 5M Series Final Tier 4 (FT4) Tractors - 5075M, 5085M, 5100M, 5115M

### CAPACITIES (Approximate):

#### Fuel Tank:

5075M-5100M (Open Operator Station).....	113 L (30 gal)
5075M-5100M (Cab) .....	136 L (36 gal)
5115M (Open Operator Station) .....	152 L (40 gal)
5115M (Cab).....	178 L (47 gal)

#### Cooling System:

##### Cool-Gard™ II

5075M (Open Operator Station).....	15 L (4 gal)
5075M (Cab).....	17 L (4.5 gal)
5085M-5115M (Open Operator Station).....	11.7 L (3.1 gal)
5085M-5115M (Cab).....	14 L (3.7 gal)

#### Crankcase with Filter:

##### Plus-50™ II

5075M.....	8.5 L (2.2 gal)
5085M-5115M.....	12.1 L (3.2 gal)

#### Transmission and Hydraulic System:

##### Hy-Gard™

5075M.....	53 L (14 gal)
5085M-5115M.....	39.4 L (10.4 gal)

#### Mechanical Front Wheel Drive (MFWD) Axle Housing:

##### Hy-Gard™

5075M.....	5.0 L (1.31 gal)
5085M-5115M.....	4.5 L (1.17 gal)

#### Mechanical Front Wheel Drive (MFWD) Hubs (Each):

##### Hy-Gard™

5075M.....	0.8 L (0.21 gal)
5085M-5115M.....	2.3 L (0.6 gal)

#### Diesel Exhaust Fluid (DEF):

##### John Deere™ Diesel Exhaust Fluid

5085M-5115M (Open Operator Station).....	13.2 L (3.48 gal)
5085M-5115M (Cab).....	18.9 L (4.99 gal)

[Return to Filter Overview](#)

