


FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

6M Final Tier 4 (FT4) MY20 Series Utility Tractors – 6110M, 6120M

CAB

RECIRCULATION AIR FILTER (QTY 2)
[L214634](#)

Replace after every 1500 hours or 2 years, whichever occurs first.



CAB

FRESH AIR FILTER (QTY 2)
[AL177184](#)


Replace after every 1500 hours or 2 years, whichever occurs first.



HYDRAULICS

OIL FILTER [AL169573](#)

Replace after first 100 hours then after first 500 hours and every 500 hours thereafter. Change Transmission Oil Filter as well.



TRANSMISSION

OIL FILTER [AL221066](#)

Replace after first 100 hours then after first 500 hours and every 500 hours thereafter. Change Transmission Oil Filter as well.



ENGINE

OIL FILTER [RE504836](#)


Replace after first 100 hours and every 500 hours thereafter or annually. The extended 500 hour interval is only allowed if using Plus-50™ II oil, JD OEM Oil Filter and diesel fuel with sulfur content less than 15mg/kg (15 ppm). Change Oil and Filter after every 250 hours, if conditions are not met.



ENGINE

CRANKCASE VENTILATION FILTER
[DZ105100](#)

Replace after every 1500 hours



ENGINE

DEF LINE FILTER [RE554498](#)

Replace after every 4500 hours or 3 years, whichever occurs first.



ENGINE

DEF INJECTION PUMP FILTER [DZ110513](#)

Replace after every 4500 hours or 3 years, whichever occurs first.



ENGINE

PRIMARY FUEL FILTER [RE560682](#)
FINAL FUEL FILTER [RE551508](#)

Replace after every 500 hours.



ENGINE

SECONDARY AIR FILTER [AL225872](#)

Replace at every fourth change of Primary Air Filter, or after 4500 hours or 2 years, whichever occurs first.



ENGINE

PRIMARY AIR FILTER [AL230505](#)

Replace after every 1500 hours or 2 years, whichever occurs first.



FRONT PTO

OIL FILTER [DE30500](#)

Replace after every 500 hours.



JOHN DEERE

Genuine Parts and Service

CAPACITIES

6M Final Tier 4 (FT4) MY20 Series Utility Tractors – 6110M, 6120M

CAPACITIES (Approximate):

Fuel Tank:

..... 175 L (46.2 gal)
..... 205 L (54.2 gal)

DEF Tank:

John Deere Diesel Exhaust Fluid™
..... 19 L (5.0 gal)

Cooling System:

Cool-Gard™ II
..... 20 L (5.3 gal)

Crankcase:

Plus-50™ II
..... 17 L (4.5 gal)

Transmission / Hydraulics:

Hy-Gard™

Transmission 60 L (15.9 gal)
Extra with creeper 2 L (0.5 gal)
Extra with front-wheel drive 3 L (0.8 gal)
Extra with additional oil reservoir 20 L (5.3 gal)

Front PTO:

..... 2.6 L (0.7 gal)

Front-wheel Drive:

Hy-Gard™

2 Piece Front Axle

Axle housing 6.4 L (1.7 gal)
Final drives, per side (with brake) 0.8 L (0.2 gal)
Final drives, per side (without brake) 1.4 L (0.4 gal)

Air-conditioning System:

R134a Refrigerant 775 - 825 g
(1.71 - 1.82 lb)

[Return to Filter Overview](#)

