

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

9450, 9550, 9650 Walker Series Combines

ENGINE

PRIMARY AIR FILTER
(9450) – [AR70106](#)

PRIMARY AIR FILTER
(9550, 9650) – [AH148880](#)

Change annually and clean or change as required.



ENGINE

SECONDARY AIR FILTER
(9450) – [AR70107](#)

SECONDARY AIR FILTER
(9550, 9650) – [RE63932](#)

Change secondary filter only with primary filter.



ENGINE

OIL FILTER (9450) – [RE59754](#)
TO6068HH052 Upto Engine Serial No.- (-892978)

OIL FILTER (9450, 9550) – [RE504836](#)
(9450) TO6068HH052 From Engine Serial No.- (832979-)
(9450) PE6068HH052 From Engine Serial No.- (178244-)
(9550) 6068 From Engine Serial No.- (215285-)

OIL FILTER (9550, 9650) – [RE57394](#)
(9550) 6081 Upto Engine Serial No.- (-156457)
(9650) Spin On Upto Engine Serial No.- (-202201)

OIL FILTER (9650) – [RE509672](#)
(9650) Top load From Engine Serial No.- (202202-)

Minimum hours before first engine oil change is 100 Hours. Extended engine oil change every 500 hours or annually, whichever come first. The extended 500 hour interval is only allowed if using Plus-50™ II oil with a John Deere filter and diesel fuel with sulfur content less than 15mg/kg (15ppm). If all conditions are not met, change oil and filter at 250 hours of operation.

CAB

RECIRCULATION AIR FILTER
(9450, 9550, 9650) – [AH115836](#)

Clean or replace every 200 hours and as required.



CAB

AIR FILTER, STANDARD
(9450, 9550, 9650) – [AH115833](#)

AIR FILTER, HEAVY DUTY
(9450, 9550, 9650) – [AH168783](#)

Clean or replace after 50 hours and as required.

HYDRAULIC / HYDROSTATIC / ENGINE GEARCASE

FILTER ELEMENT
(9450, 9550, 9650) – [AH128449](#)

Replace every 400 hours or yearly.
Note: Replace all three filters at a time.



ENGINE

FUEL FILTER (9450) – [RE62419](#)

FUEL FILTER (9550, 9650) – [AR86745](#)
(9550) 6081 Upto Engine Serial No.- (-156457)
(9650) Upto Engine Serial No.- (-199999)

FUEL FILTER (9550) – [RE509032](#)
Upto Engine Serial No.- (-215285)

FUEL FILTER (9650) – [RE522372](#)
From Engine Serial No.- (200000-), Single Filter System.

PRIMARY FUEL FILTER (9650) – [RE531703](#)
From Engine Serial No.- (200000-), Dual Filter System

SECONDARY FUEL FILTER (9650) – [RE522688](#)
From Engine Serial No.- (200000-), Dual Filter System

FUEL PRESCREEN (9650) – [RE507011](#)
From Engine Serial No.- (202102-)

FUEL WATER SEPARATOR FILTER
(9450, 9550, 9650) – [RE500186](#)

FUEL FILTER (9450) – [AM107314](#)

FUEL FILTER (9550) – [AM107314](#), [RE509036](#)
From Engine Serial No.- (700701-)

FUEL FILTER – [R502778](#)
Engine Serial No.- (20000-232462)

FUEL FILTER (9650) – [R502778](#)
From Engine Serial No.- (695407-) Also for 695394, 695395, 695401, 695402, 695405

Replace every 500 hours and as required.



JOHN DEERE
Genuine Parts and Service

CAPACITIES

9450, 9550, 9650 Walker Series Combines

CAPACITIES (Approximate):

Fuel Tank:

9450, 9550, 9650..... 565 L (149 gal)

Cooling System with Heater:

Cool-Gard™

9450..... 36 L (9.5 gal)

9550 (-695200), 9650 (-695300) 38 L (10.03 gal)

9550 (700201 -) 40 L (10.6 gal)

Engine Crankcase with Filter:

Torq-Gard Supreme™ or Plus-50™ II

9450..... 18.9 L (5 gal)

9550 (-695200), 9650 28.5 L (7.5 gal)

9550 (700201 -) 32 L (8.5 gal)

Transmission:

GL-5

9450, 9550, 9650..... 9.6 L (2.5 gal)

Final Drives (Each):

GL-5

9450, 9550..... 8.5 L (2.2 gal)

9650 Regular Duty Single Reduction 8.5 L (2.2 gal)

9650 Heavy Duty Single Reduction..... 3.8 L (1 gal)

Feeder House Reverser Gearcase:

GL-5

9450 (-695100), 9550 (-695200), 9650 (-695300)
..... 0.9 L (0.23 gal)

Feeder House Reverser Gearcase without Cooler:

GL-5

9450 (700101 -) 9550 (700201 -) and 9650 (700301 -)
..... 2.3 L (0.6 gal)

Feeder House Reverser High-Capacity with Cooler:

GL-5

9550-9650 3.5 L (0.9 gal)

Primary Countershaft Drive Gearcase:

GL-5

9450, 9550, 9650..... 1.2 L (0.3 gal)

Straw Walker Drive Gearcase:

John Deere Corn Head Grease

9450, 9550, 9650..... 0.4 L (0.1 gal)

Dual-Range Cylinder Drive Gearcase:

GL-5

9450, 9550, 9650..... 1.9 L (0.5 gal)

Engine Gearcase:

Low Viscosity Hy-Gard™

9450, 9550, 9650..... 16 L (4.2 gal)

Loading Auger Gearcase:

GL-5

9450, 9550, 9650..... 3.8 L (1 gal)

Hydraulic / Hydrostatic Reservoir:

Low Viscosity Hy-Gard™

9450, 9550, 9650..... 34 L (9 gal)

[Return to Filter Overview](#)

