

FILTER OVERVIEW WITH SERVICE INTERVALS AND CAPACITIES

9R Four Wheel Drive Final Tier 4 (FT4) Series Tractors - 9370R, 9420R, 9470R, 9520R, 9570R & 9620R

ENGINE

DIESEL PARTICULATE FILTER (DPF)
[DZ100174](#) - 9370R (SIZE 6)
[RE561840](#) - 9370R (SIZE 7)
[DZ100175](#) - 9420R, 9470R, 9520R (SIZE 7)
[RE561844](#) - 9420R, 9470R, 9520R (SIZE 8)
[REC550603000](#) - 9570R, 9620R

Replace within 250 hours after warning light indicators are illuminated. See your John Deere™ dealer or qualified service provider.

ENGINE

CRANKCASE BREATHER FILTER ELEMENT (15L)
[RECCV5063400](#)

Replace after every 3000 hours.

ENGINE

OIL FILTER (9570R & 9620R)
[RE574468](#) (FT4)

Replace after every 500 hours or as indicated, whichever occurs first.

(Click here for [capacity](#))

ENGINE

OIL FILTER
[RE572785](#) (9420R, 9470R & 9520R) (T2, T3, FT4)
[RE509672](#) (9370R) (T2, FT4)
[RE572785](#) (9570R) (T2, T3)

Replace after every 500 hours or as indicated, whichever occurs first.

(Click here for [capacity](#))

ENGINE

(9370R)
PRIMARY FUEL FILTER [RE539465](#) (FT4)
SECONDARY FUEL FILTER [DZ112918](#) (FT4)
PRIMARY & SECONDARY FUEL FILTER
[RE525523](#) (T2)

(9420R, 9470R & 9520R)
PRIMARY FUEL FILTER [RE539465](#) (FT4)
PRIMARY FUEL FILTER [RE532952](#) (T2, T3)
SECONDARY FUEL FILTER
[DZ112918](#) (T2, T3 & FT4)

Replace after every 500 hours, or as indicated, whichever occurs first.

CAB

RECIRCULATION FILTER
[RE291412](#)
[RE333569](#) (Carbon)

Replace after every 1000 hours or annually, whichever occurs first.

CAB

FRESH AIR FILTER
[RE284091](#)
[RE333567](#) (Carbon)

Replace after every 1000 hours or annually, whichever occurs first.

ENGINE

FUEL WATER SEPARATOR FILTER
 (If equipped) - [N378886](#) (- 0666447)
[AT365869](#) (064448 -) (Except 9620R)

Change after every 500 hours.

SCV

OIL FILTER - [RE269061](#)
 Replace after every 1500 hours.

HYDRAULIC

TRANSMISSION SYSTEM FILTER - [RE577250](#)
TRANSMISSION LUBE FILTER - [RE577612](#)
 Replace after every 1500 hours or annually, whichever occurs first.

ENGINE

FUEL TANK VENT FILTERS
[RE566125](#) (QTY 2)
 Replace after every 1500 hours.

HYDRAULIC OIL FILTER

SINGLE REDUCTION AXLE
[RE577612](#) - Qty. 2
DOUBLE REDUCTION AXLE
[RE577612](#) - Qty. 3
 Replace after every 1500 hours.
 (Click here for [capacity](#))

ENGINE

DEF TANK HEADER FILTER
[DZ111004](#)
 Replace after every 4500 hours.

ENGINE

DEF SUPPLY MODULE FILTER
[DZ114640](#)
 Replace after every 3000 operating hours or 3 years, whichever comes first.

ENGINE

DEF INLINE FILTER
[DZ100304](#) (- 062000)
[DZ110513](#) (062001 -)
 Replace after every 1000 hours or annually, whichever occurs first.

ENGINE

DEF TANK VENT FILTER [H216169](#)
 Replace after 1500 hours or 1 year whichever occurs first.

ENGINE

PRIMARY AIR FILTER
[RE594852](#) - Qty. 2 (FT4)
[HXE11090](#) - Qty. 1 (T2, T3)

Replace after every 1000 hours or annually, whichever occurs first.

ENGINE

SECONDARY AIR FILTER
[RE594853](#) - QTY2 (FT4)
[RE594853](#) - (-064002) QTY2 (T2, T3)
[HXE11091](#) - (064003-) QTY1 (T2, T3)

Replace after every 1000 hours or annually, whichever occurs first.



JOHN DEERE
 Genuine Parts and Service

https://www.deere.com/en_US/parts/parts_by_industry/ag/fmi/filter_maintenance_information.page

CAPACITIES

9R Four Wheel Drive Final Tier 4 (FT4) Series Tractors - 9370R, 9420R, 9470R, 9520R, 9570R & 9620R

CAPACITIES (Approximate):

Fuel Tank:

9370R, 9420R & 9470R - SR Axles.....	1173 L (310 gal)
9520R, 9570R & 9620R - DR Axles	1514 L (400 gal)

Cooling System Including Overflow Tank:

Cool-Gard™ II

9370R.....	50 L (13.2 gal)
9420R, 9470R & 9520R	56.5 L (14.9 gal)
9570R & 9620R.....	62 L (16.3 gal)

Crankcase including Filter:

Plus-50™ II

9370R.....	34 L (9.0 gal)
9420R, 9470R & 9520R	48 L (12.7 gal)
9570R & 9620R.....	43.5 L (11.5 gal)

Diesel Exhaust Fluid John Deere Diesel Exhaust Fluid™

.....	83 L (22.0 gal)
-------	-----------------

Hydraulic Reservoir:

Hy-Gard™

Full - Cold	93 L (24.5 gal)
Min - Cold	81 L (21.5 gal)

Transmission/Hydraulic Reservoir:

Hy-Gard™

9370R, 9420R & 9470R - SR Axles Stand. Flow.....	265 L (70 gal)
9370R, 9420R & 9470R - SR Axles High Flow.....	268.5 L (71 gal)
9520R, 9570R & 9620R - DR Axles Stand. Flow	208 L (55 gal)
9520R, 9570R & 9620R - DR Axles High Flow	212 L (56 gal)

Hydraulic/Transmission/Axle without 3-point rear hitch and PTO

Hy-Gard™

9370R, 9420R & 9470R	276 L (73 gal)
9520R, 9570R & 9620R	220 L (58 gal)

Hydraulic/Transmission/Axle with 3-point rear hitch and PTO

Hy-Gard™

9370R, 9420R & 9470R	284 L (75 gal)
9520R, 9570R & 9620R	227 L (60 gal)

[Return to Filter Overview](#)

